



200 gr/m², 65% Polyester
35% Cotton, VAT Dyed,
Chemical Resistant,
2/1S Twill Fabric



Sample



**ArWoWear T4 Chem Pro -
4663 Orange****ArWoWear T4 Chem Pro -
4664 Dark Green****ArWoWear T4 Chem Pro -
4665 Red****ArWoWear T4 Chem Pro -
4667 Dark Blue****ArWoWear T4 Chem Pro -
4668 Black****ArWoWear T4 Chem Pro -
4669 Navy****ArWoWear T4 Chem Pro -
4671 Grey**

Description

ArWoWear T4 Chem Pro is 200 gr/m², vat dyed, 65% polyester 35% cotton merserized workwear fabric.
It is usefull for outdoor summer hard working conditions.
Water and oil repellent (TS EN ISO 4920) function.
It is resistant to most industrial chemicals (EN ISO 13034).

Technical Parameters

Name	Values	Standards
Fiber	65% Polyester (PES) 35% Cotton (CO)	EN ISO 2076
Yarn	Warp:20/1Ne; Weft:20/1Ne	EN ISO 2060
Weight	200 ±5 gr/m ²	EN ISO 3081
Width	1600 ±20 mm	EN ISO 3932
Tensile Strength	Warp>800N; Weft>600N	EN ISO 13934-1
Tear Strength	Warp>20N; Weft>15N	EN ISO 13937-2
Dimensional Change	-3%<Length<+3%;-3%<Width<+3%	EN ISO 5077
Rubbing Fastness	4-5	EN ISO 105 X12
Perspiration Fastness	4-5	EN ISO 105 E04
Washing Fastness	4-5	EN ISO 105 C06
Dry Cleaning Fastness	4-5	EN ISO 105 D01
Hypochlorite Fastness	4-5	EN ISO 105 N01
Peroxide Fastness	4-5	EN ISO 105 N02
Hot Press Fastness	4-5	EN ISO 105 X11
Light Fastness	6-7	EN ISO 105 B02
Perspiration Light Fast.	4-5	EN ISO 105 B07
pH	6.0	EN ISO 3071
Azo Test	No Azo Colorants.	EN ISO 14362-1
Application	Coveralls	
Quality Management	Done	ISO 9001
Chemical Resistant	Yes	EN ISO 13034